



SPECIFICATION

- 1. Rated Voltage 1.5V
- 2. Operating Voltage 2~7V
- 3. Max. Rated Current 30mA
- 4. Coil Resistance 16±2 Ω
- 5. Coil Impedance 40 Ω
- 6. Min. Sound Pressure Level 85dB/10cm
- 7. Resonant Frequency 2048Hz
- 8. Case Material/Color NORYL/Black
- 9. Operating Temperature -20~+60°C
- 10. Store Temperature -30~+70°C
- 11. Weight 2g

Compliance with ROHS			
KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com			
Magnetic Buzzer QUARTZ			
DAPG1285A			
<small>UNIT</small>	mm	<small>DWG. NO.</small>	OEM1868R
<small>SCALE</small>	NOT TO SCALE	<small>SHEET</small>	VER 1.0

No.	DESCRIPTION	APPROVED	DATE
<small> TOLERANCES UNLESS NOTED OTHERWISE: .X * .XX * .XXX * 90° FORMED ±.2° ANGLES ±.1° FIRST ANGLE PROJECTION </small>		<small>APPROVALS</small>	<small>DATE</small>
		<small>DRAWN</small>	
		<small>CHECKED</small>	
		<small>APPROVED</small>	06.08.28